

UTING®

NAGATA

Digital Crane Scales

Since 1955

**Designed for
High Safety,
Accuracy,
Durability,
& Productivity!**

Optional TICKET PRINTER:



Saat: 14:55:51 Tarih: 30/01/2014
TARTIM TOPLAMI

No	Tarih	Saat	Tartim	TOPLAM
1	30/01/2014	14:55	41	41
2	30/01/2014	14:55	75	116
3	30/01/2014	14:55	29	145
4	30/01/2014	14:55	97	242

**Super bright LED display
360° swivel hook (1-30 T.)**

Unbeatable high resolution of 1/5000

Wide range of capacities:0,3-50 Ton

Battery life of up to 150 hours

3 Patent awards ...

Remote Control:

- * On-Off
- * Zero / Tara
- * Change Increment
- * Add / Print Ticket
- * Subtract / Print Total

NAGATA Patented Load Cell:

**One-piece, overload protected design
(U.S. Patent Nr: 5591943)**

Patented Safe Device:

**Upper ring and hook no-screw connection
(T. Patent Nr:050049)**

Patented Remote Control:

Enhanced 6 pushbutton safe operation (T. Patent Nr:75712)



**Optional wireless desktop printicator
with display for weight watching,
single ticket & total printing, zeroing**



UTING® - NAGATA

DIGITAL CRANE SCALES



TECHNICAL SPECIFICATIONS:

HA-03 (0.3~1T)

- o High impact ABS housing
- o Super bright 0.6" LED display
- o Rechargeable battery 6V / 4A & Charger (~130 hours duration)

Capacity - Increment

300Kg	- 100gr
600Kg	- 200gr
1T	- 500gr

HB-03 (1.5~2T)

- o Cast Aluminium alloy housing
- o Super bright 1.0" LED display
- o Rechargeable battery 6V / 10A & Charger (~150 hours duration)

Capacity - Increment

1T	- 500gr
1.5T	- 500gr
2T	- 1Kg
2.5T	- 1Kg

HC-03 (3~15T)

- o Cast Aluminium alloy housing
- o Super bright 1.2" LED display
- o Rechargeable battery 6V / 10A & Charger (~150 hours duration)
- o Remote Control

Capacity - Increment

3T	- 1Kg
5T	- 2Kg
7.5T	- 2Kg
10T	- 5Kg
15T	- 5Kg

HL-03 (15~100T)

- o Cast Aluminium alloy housing
- o Super bright 2.3" LED display
- o Rechargeable 2 batteries 12V / 7A & Charger (~150 hours duration)
- o Remote Control

Capacity - Increment

15T	- 5Kg
20T	- 10Kg
25T	- 10Kg
30T	- 10Kg
40T	- 20Kg
50T	- 20Kg

OPTIONAL ITEMS:

HEAT RESISTANCY KIT

Safe distance:

1000°C	1.5 mt.
1200°C	1.8 mt.
1400°C	2.0 mt.
1600°C	2.5 mt.

for HB/HC/HL models

PRINTER

Embedded thermal printer

PRINTICATOR

Wireless Desktop printer with display (for up to 500m)

CAB-10

RS-232 serial output for computer with 10m cable

BIG DISPLAY

Wireless display with 100mm digits



UTING®
ELEKTRONIK

UTING ELEKTRONIK ve ENDÜSTRİYEL
ÜRÜNLER, MÜMESSİLLİK, DIŞ TİC.
ve SAN. LTD.ŞTİ.

Tel: +90-212-639 20 95-97
Fax: +90-212-639 32 19
E-mail: mail@utingelektronik.com
Web: www.utingelektronik.com